

Amendments to the Claims:

This listing of Claims will replace all prior versions, and listings, of Claims in the Application:

Listing of Claims:

Claims 1-26 (Canceled)

Claim 27 (Currently Amended) A male fastener, comprising:

- a) a shaft that includes an axis, a first end, and a second end;
- b) the shaft provided with a first threaded surface and a second threaded surface;
- c) the first threaded surface includes a trilobular cross-sectional shape and a plurality of threads, including a first locking thread, a first Vee-shaped thread and a first curved thread;
- d) the second threaded surface includes a trilobular cross-sectional shape and a plurality of threads, including a second locking thread, a second Vee-shaped thread and a second curved thread;
- e) the first curved thread extends from the first end of the shaft;
- f) the second curved thread extends from the second end of the shaft;
- g) the first locking thread is located adjacent to the first curved thread and configured to structurally reform threads of a first mating member; and
- h) the second locking thread is located adjacent to the second curved thread and configured to structurally reform threads of a second mating member.

Claim 28 (Previously Presented) A male fastener according to claim 27, wherein at least one of the locking threads is provided with a root surface that is angled relative to the axis of the shaft.

Claim 29 (Previously Presented) A male fastener according to claim 27, wherein at least one of the locking threads is provided with a root surface that is at an angle between four and eight degrees relative to the axis of the shaft.

Claim 30 (Currently Amended) A male fastener according to claim 27, wherein at least one of the curved threads is located between the [a] Vee-shaped thread and the second end of the male fastener.

Claim 31 (Previously Presented) A male fastener according to claim 27, wherein at least one of the curved threads includes a curved surface located between a first side and a second side.

Claim 32 (Previously Presented) A male fastener according to claim 27, wherein at least one of the curved threads includes a curved surface located between a first side that is curved and a second side that is curved.

Claim 33 (Canceled)

Claim 34 (Previously Presented) A male fastener according to claim 27, further comprising a conical surface that is provided on the male fastener.

Claim 35 (Previously Presented) A male fastener according to claim 27, further comprising a conical surface and cylindrical surface that are provided on the male fastener.

Claim 36 (Canceled)

Claim 37 (Previously Presented) A male fastener according to claim 27, wherein:

- a) at least one of the mating members is a nut body rotatable about the axis of the shaft that includes:
 - i) an annular surface on the nut body provided with a plurality of inclined faces oriented circumferentially forming portions of an undulating annular surface; and
 - ii) a washer body rotatable relative to the nut body and provided with a bearing surface and a clamping surface, wherein the clamping surface includes a plurality of protrusions and the bearing surface is axially opposed to the annular surface on the

nut body and provided with a plurality of inclined faces oriented circumferentially and forming portions of an undulating bearing surface.

Claim 38 (Currently Amended) A male fastener, comprising:

- a) a shaft that includes an axis, a first end, and a second end;
- b) the shaft includes a first threaded surface and a second threaded surface;
- c) the first threaded surface is provided with a cross-sectional shape that is trilobular and includes a first locking thread, a first Vee-shaped thread and a first lead thread including means for guiding a first female member;
- d) the second threaded surface is provided with a cross-sectional shape that is trilobular and includes a second locking thread, a second Vee-shaped thread and a second lead thread including means for guiding a second female member;
- e) the first lead thread extends from the first end of the shaft;
- f) the second lead thread extends from the second end of the shaft;
- g) the first locking thread is located adjacent to the first lead thread and configured to structurally reform threads of a first female member; and
- h) the second locking thread is located adjacent to the second lead thread and configured to structurally reform threads of the second female member.

Claim 39 (Previously Presented) A male fastener according to claim 38, wherein at least one of the locking threads is provided with a root surface that is angled relative to the axis of the shaft.

Claim 40 (Previously Presented) A male fastener according to claim 38, wherein at least one of the locking threads is provided with a root surface that is at an angle between four and eight degrees relative to the axis of the shaft.

Claim 41 (Currently Amended) A male fastener according to claim 38, wherein at least one of the lead threads is located between the [a] Vee-shaped thread and the second end of the male fastener.

Claim 42 (Currently Amended) A male fastener according to claim 38, wherein at least one of the lead threads is provided with a reduced diameter relative to the [a] Vee-shaped thread.

Claim 43 (Previously Presented) A male fastener according to claim 38, wherein at least one of the lead threads is located adjacent to a plateau thread.

Claim 44 (Previously Presented) A male fastener according to claim 38, wherein the at least one of the lead threads is located adjacent to a plateau thread that is provided with a ramped cross-sectional profile.

Claim 45 (Canceled)

Claim 46 (Previously Presented) A male fastener according to claim 38, further comprising a conical surface that is provided on the male fastener.

Claim 47 (Previously Presented) A male fastener according to claim 38, further comprising a conical surface and cylindrical surface that are provided on the male fastener.

Claim 48 (Canceled)

Claim 49 (Previously Presented) A male fastener according to claim 38, wherein:

- a) at least one of the female members is a nut body rotatable about the axis of the shaft that includes:
 - i) an annular surface on the nut body provided with a plurality of inclined faces oriented circumferentially forming portions of an undulating annular surface; and
 - ii) a washer body rotatable relative to the nut body and provided with a bearing surface and a clamping surface, wherein the clamping surface includes a plurality of protrusions and the bearing surface is axially opposed to the annular surface on the

nut body and provided with a plurality of inclined faces oriented circumferentially and forming portions of an undulating bearing surface.

Claim 50 (Currently Amended) A stud, comprising:

- a) a shaft that includes an axis, a first end, and a second end;
- b) the shaft is provided with a first threaded surface and a second threaded surface;
- c) the first threaded surface includes a trilobular cross-sectional shape and a plurality of threads, including a first locking thread, a first Vee-shaped thread and a first curved thread;
- d) the second threaded surface includes a trilobular cross-sectional shape and a plurality of threads, including a second locking thread, a second Vee-shaped thread and a second curved thread;
- e) the first curved thread extends from the first end of the shaft;
- f) the second curved thread extends from the second end of the shaft;
- g) the first locking thread is configured to structurally reform threads of a first mating member; and
- h) the second locking thread is configured to structurally reform threads of a second mating member.

Claim 51 (Previously Presented) A stud according to claim 50, wherein at least one of the locking threads is provided with a root surface that is angled relative to the axis of the shaft.

Claim 52 (Previously Presented) A stud according to claim 50, wherein at least one of the locking threads is provided with a root surface that is at an angle between four and eight degrees relative to the axis of the shaft.

Claim 53 (Currently Amended) A stud according to claim 50, wherein at least one of the curved threads is located between the [a] Vee-shaped thread and the second end of the stud.

Claim 54 (Previously Presented) A stud according to claim 50, wherein at least one of the curved threads includes a curved surface located between a first side and a second side.

Claim 55 (Previously Presented) A stud according to claim 50, wherein at least one of the curved threads includes a curved surface located between a first side that is curved and a second side that is curved.

Claim 56 (Canceled)

Claim 57 (Previously Presented) A stud according to claim 50, further comprising a conical surface that is provided on the stud.

Claim 58 (Previously Presented) A stud according to claim 50, further comprising a conical surface and cylindrical surface that are provided on the stud.

Claim 59 (Canceled)

Claim 60 (Previously Presented) A stud according to claim 50, wherein:

- a) at least one of the mating members is a nut body rotatable about the axis of the shaft that includes:
 - i) an annular surface on the nut body provided with a plurality of inclined faces oriented circumferentially forming portions of an undulating annular surface; and
 - ii) a washer body rotatable relative to the nut body and provided with a bearing surface and a clamping surface, wherein the clamping surface includes a plurality of protrusions and the bearing surface is axially opposed to the annular surface on the nut body and provided with a plurality of inclined faces oriented circumferentially and forming portions of an undulating bearing surface.